CLR BRANDS[®] STAINLESS STEEL

DESCRIPTION

CLR Brands® Stainless Steel removes dirt, residue and fingerprints in many industrial and commercial uses including stainless steel appliances, elevators and work stations.

FEATURES & BENEFITS

- One step, ready-to-use powerful foaming action
- NSF Registered—approved for use in food processing, food storage, and food service facilities
- Leaves no fingerprints, residue, or streaks
- Cleans and protects and leaves behind a shiny protective barrier that repels dust, dirt, and grime
- Water-based



- 1. Spot test on inconspicuous area.
- 2. Appliances should be turned off and cool
- Wipe or clean any residual cleaning product before using CLR Brands® Stainless Steel
- 4. Shake well before each application
- 5. Hold can 6 inches from surface and spray lightly
- 6. Wipe area with clean soft cloth
- 7. Heavily soiled areas may need a second application

Product	Size	Stock #
CLR Brands® Stainless Steel	12 oz. aerosol can	CSS-12

Safety: See label and SDS for precautionary instructions before use. Use appropriate safety equipment and job site controls during application, handling, and disposing. SDS is available online at **www.clrpro.com**.





DIIVCI	c λ i 0	CHEMICAL	PROPERTIES
PEVSI	$I \cap A = X_{\ell}$		PRIDERILES
	CALG	CHEMICAL	

Appearance	Gas, colorless
Odor	N.A.
OdorThreshold	N.A.
рН	N.A.
Melting Point/Freezing Point	N.A.
Initial Boiling Point and Range	134.79°C (274.61°F)
Flash Point	-104.4°C (-156.0°F)
Evaporation Rate	N.A.
Flammability (solid, gas)	N.A.
Flammability Limit, Upper/Lower	9.5% / 1.9%
Explosive Limit, Upper/Lower	N.A.
Vapor Pressure	45-65 psig @21°C (70°F)
Vapor Density	N.A.
Relative Density	N.A.
Solubility (Water)	N.A.
Partition Coefficient; n-octanol/water	N.A.
Auto-ignition Temperature	N.A.
Decomposition Temperature	N.A.
Viscosity	N.A.
Explosive Properties	Not Explosive
Oxidizing Properties	Not Oxidizing
Specific Gravity	0.82 estimated

TDS-CSS-0225

